



PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

***Servicios Industriales y de Apoyo de la Laguna, S.A. de C.V.
(SIA Calibración)***

***Calzada Hacienda el Rosario # 4 Local 8, Residencial Hacienda el Rosario
Torreón, Coahuila, México. C.P. 27019***

*(Hereinafter called the Organization) and hereby declares that Organization is accredited
in accordance with the recognized International Standard:*

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the
operation of a laboratory quality management system
(as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

***Dimensional Inspection and Electrical Testing
(As detailed in the supplement)***

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Initial Accreditation Date:

Issue Date:

Expiration Date:

February 12, 2014

November 07, 2022

December 31, 2024

Tracy Szerszen
President

Accreditation No.:

Certificate No.:

72789

L22-744

Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan 48084

*The validity of this certificate is maintained through ongoing assessments based
on a continuous accreditation cycle. The validity of this certificate should be
confirmed through the PJLA website: www.pjlabs.com*



Certificate of Accreditation: Supplement

Servicios Industriales y de Apoyo de la Laguna, S.A. de C.V. (SIA Calibración)

Calzada Hacienda el Rosario # 4 Local 8, Residencial Hacienda el Rosario
Torreón, Coahuila, México. C.P. 27019
Contact: Carlos Armando Herrera Phone: 871-204-4033

Accreditation is granted to the facility to perform the following Testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Dimensional Inspection ^F	Parts and Products	GD&T	ASME Y14.5 CMM	X= 1 mm to 700 mm Y= 1 mm to 1 000 mm Z= 1 mm to 600 mm (Res.= 0.001 mm)
Dimensional Inspection ^{FO}			ASME Y14.5 PCMM	X= 1 mm to 3 000 mm Y= 1 mm to 3 000 mm Z= 1 mm to 3 000 mm (Res.= 0.025 mm)
			ASME Y14.5 Faro Scanner	X= 1 mm to 3 000 mm Y= 1 mm to 3 000 mm Z= 1 mm to 3 000 mm (Res.= 0.02 mm)
Electrical ^{FO}	Electrical Boards and Devices	DC Voltage	EA-10/15 NOM-127-SCFI Fluke 376	100 mV to 1 000 V
		DC Current		100 mA to 999.9 A
		AC Voltage		100 mV to 1 000 V
		AC Current		100 mA to 999.9 A
		Resistance		1 Ω to 60 000 Ω

1. The presence of a superscript F means that the laboratory performs calibration of the indicated parameter at its fixed location. Example: Outside Micrometer^F would mean that the laboratory performs this calibration at its fixed location.
2. The presence of a superscript FO means that the laboratory performs testing of the indicated parameter both at its fixed location and onsite at customer locations. Example: Outside Micrometer^{FO} would mean that the laboratory performs this testing at its fixed location and onsite at customer locations.